

Technical Information



Location

700 W. Rio Salado Parkway
Tempe, AZ 85281

Loading Dock

700 W. Rio Salado Parkway
Dock: South side of building
Door: Upstage (southwest corner) 10'W x 14'H

General Information

Flexible seating with maximum capacity of 235

• STAGE SPECIFICATIONS

Configurations

End of stage specifications:

Audience to back wall.....33'
Wall to wall w/o draperies 51.5'
Floor to catwalks21'

Seating capacity: 207 w/balcony; 235 w/extra front rows

Thrust specifications:

Audience to back wall..... 48'
Side audience to audience 20-51.5'
Floor to catwalks 21'

Seating capacity: 200 w/balcony

Arena specifications:

Playing space19.5' x 19.5'
Floor to catwalks21'

Seating capacity: 211 w/balcony

Dressing Rooms

2 – 8-person room with showers

Wardrobe

Washers (2) and dryers (2) available

Draperies

All other curtains are black velour and sewn flat

Border: 2 panels 51'W x 5'H
Borders: 2 panels51'W x 9'H
Legs: 8 panels 12'W x 21'H
Traveler: 4 panels.....25'W x 21'H
Side Tabs: 4 panels 16'6"W x 21'H
Scrim (Black Sharkstooth): 1 panel 1 panel 51'W x 21' H
Cyclorama (White filled Leno): 1 panel..... 1 panel 51'W x 21'H

• LIGHTING

Lighting Console: ETC Expression 3 Emphasis

Control Location: Front of house booth

Balcony Level

Dimmers:..... 240 2.4k ETC Sensor Racks
Company Switch:400Amp-3phase

Instruments

10	Source 4	19 Degree
26	Source 4	26 Degree
58	Source 4	36 Degree
38	Source 4	50 Degree
32	Source 4	Par
10	FC1	4 Circuit Cyc Light

Cables

36	Twofers
38	5' Cable
12	10' Cable
14	25' Cables
8	50' Cables
2	100' Cables
10	10'x6 Circuit Multi Cable
27	25'x6 Circuit Multi Cable
2	100'x6 Circuit Multi Cable
30	10' Male Veam to Female Pin Fan Out
1	3 Phase Cam Lock Tails
1	3 Phase Cam Lock 30' Feeder Cable

Accessories (shared with the Theater)

80	6" Top Hats	Pars
340	6" Top Hats	Source 4s
425	A size Pattern Holders	
21	7.5" Color Scroller	
4	6 way Power supply	
52	24" Sidearms w/2 sliding Tee	
30	12" Sidearms w/1 sliding Tee	
20	Iris Kits (source 4)	
8	50lb Boom Base and 12' x 1.5" Boom Pipe	
18	Scenery Bumpers	



Contact

Kathleen Dooner
 480-350-2877
 kathleen_dooner@tempe.gov

• **STAGE SPECIFICATIONS**

Configurations

End of stage specifications:

Audience to back wall.....33'
 Wall to wall w/o draperies 51.5'
 Floor to catwalks 21'

Seating capacity: 207 w/balcony; 235 w/extra front rows

Thrust specifications:

Audience to back wall..... 48'
 Side audience to audience 20-51.5'
 Floor to catwalks 21'

Seating capacity: 200 w/balcony

Arena specifications:

Playing space 19.5' x 19.5'
 Floor to catwalks 21'

Seating capacity: 211 w/balcony

Dressing Rooms

2 – 8-person room with showers

Wardrobe

Washers (2) and dryers (2) available

Draperies

All other curtains are black velour and sewn flat

Border: 2 panels 51'W x 5'H
 Borders: 2 panels 51'W x 9'H
 Legs: 8 panels 12'W x 21'H
 Traveler: 4 panels..... 25'W x 21'H
 Side Tabs: 4 panels 16'6"W x 21'H
 Scrim (Black Sharktooth): 1 panel 1 panel 51'W x 21' H
 Cyclorama (White filled Leno): 1 panel 1 panel 51'W x 21'H

• **LIGHTING**

Lighting Console: ETC Expression 3 Emphasis

Control Location: Front of house booth

Balcony Level

Dimmers:..... 240 2.4k ETC Sensor Racks
 Company Switch: 400Amp-3phase

Instruments

10	Source 4	19 Degree
26	Source 4	26 Degree
58	Source 4	36 Degree
38	Source 4	50 Degree
32	Source 4	Par
10	FC1	4 Circuit Cyc Light

Cables

36 Twofers
 38 5' Cable
 12 10' Cable
 14 25' Cables
 8 50' Cables
 2 100' Cables
 10 10'x6 Circuit Multi Cable
 27 25'x6 Circuit Multi Cable
 2 100'x6 Circuit Multi Cable
 30 10' Male Veam to Female
 Pin Fan Out
 1 3 Phase Cam Lock Tails
 1 3 Phase Cam Lock 30'